V 5 2 0 0 L B

Violin microphone for live performance

The V 5200 LB is designed especially for large live productions where acoustic feedback from stage monitors and PA's as well as acoustic bleed from other instruments often is a problem.

ΡΙΑϹΕΜΕΝΤ







O World's Highest feedback suppression*

- O Highest suppression of ambient sound fields
- O High definition condenser microphone
- O Fast transient / attack response with low bouncing effect
- O Accurate & natural sound response
- O Easy to mount / unmount
- O Microphone can stay on instrument during sessions
- O New technologies

DATA

Technology: SAM (Soundboard Area Microphone) Working principle: Vector-based pressure gradient Cartridge type: High definition pre-polarized condenser element Cartridge technology: Direct balanced Orientation: Unidirectional / Omnidirectional Directional characteristics: Proximity- & transition- zone: half spherical Ambient zone: Omnidirectional, -20dB

Frequency Bandwidth: 10Hz – 22 KHz Max Sound pressure level: 164 dB SPL (before clip) THD : 0.5% @ 144 dB SPL [@48Vdc]* Sensitivity: 3mV/Pa: (-50dB re.1V/Pa) Self noise:-71dBu @ 20°C [equal 22dBA measured] S/N: nom. 90dB Power: 48 Vdc Phantom Power consumption: 2mA

Physical dimensions: 20 x 22 x 30mm (HxWxL) Weight: 6g (mic.only) | 55g (mic+cable+connector) Cable: Ø 3.5mm | 1.8m shielded dual pairs with cotton woven outer jacket Connector: 3 pol NEUTRIK Audio connector (Male) **NEW** instrument microphones for live performance ensuring world's highest gain before feedback.



REMIC Microphones available for violin/viola, cello/violone and upright bass

READ MORE AT WWW.remic.dk

EXPRESS YOUR ART

$\mathbf{R}_{\mathbf{M}} \mathbf{R} \mathbf{R} \mathbf{E} \mathbf{M} \mathbf{M} \mathbf{I} \mathbf{C} \mathbf{R} \mathbf{O} \mathbf{P} \mathbf{H} \mathbf{O} \mathbf{N} \mathbf{E} \mathbf{S}$

All products and publications of REMIC MICROPHONES are subject to change without notice.